

GO-GO[®] *es* 2

3-WHEEL SCOOTER

OUTSTANDING
VALUE.
EXCEPTIONAL
DURABILITY.

The Go-Go[®] ES 2 from Pride[®] combines exceptional value and easy transportation together in a compact, lightweight package. The stylish Go-Go ES 2 has a weight capacity of 250 lbs., variable motor speeds and a convenient canvas basket located on the tiller.



Go-Go[®] ES 2 3-wheel



 facebook.com/PrideMobilityProductsCorp

 youtube.com/PrideMobility

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com

SPECIFICATIONS

GO-GO® ES 2

| | |
|---------------------------------------|---|
| Weight capacity: | 250 lbs. |
| Maximum speed ¹ : | Up to 4 mph |
| Ground clearance ² : | 1.5" at motor |
| Turning radius ² : | 31" |
| Overall length ² : | 36.75" |
| Overall width ² : | 19.5" |
| Front tires: | 2" x 7.5" solid |
| Rear tires: | 3" x 7.5" solid |
| Range per charge ^{2,4} : | Up to 6 miles |
| Total weight without batteries: | 58.4 lbs. |
| Heaviest piece when disassembled: | 41.4 lbs. (scooter base) |
| Standard seating: | Type: Foldable, compact, vinyl-covered molded plastic Weight: 17 lbs. Material: Black Vinyl Dimensions: Width: 17" Depth: 15" |
| Motor output: | 24-volt DC motor, sealed mini-transaxle |
| Brakes: | Electronic, regenerative and electromechanical |
| Battery requirements ^{3,5} : | (2) 12V deep-cycle Size: (2) 10 AH Weight: 6 lbs. each |
| Battery charger: | Off-board, 2 amp |

Color:



Black

FEATURES

- Two speed settings - high and low (indoor/outdoor)
- Modular design for easy serviceability
- Removable front canvas basket
- Lightweight, one-piece frame for added stability and easy portability

Pride® Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus
- Backpacker® AVP
- Olympian
- Outlander Full Platform
- Outlander TM

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- ² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- ³ AGM or gel cell type required.
- ⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- ⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com