

3 & 4-WHEEL SCOOTER

# THE SMOOTHEST RIDE IN TRAVEL MOBILITY



Comfort-Trac Suspension

The Go-Go® LX with Comfort-Trac Suspension (CTS) brings a whole new level of comfort and performance to travel mobility scooters. Pride's industry first CTS technology incorporates advanced suspension components for improved absorption over various terrains. The Go-Go LX with CTS offers a 300 lb. weight capacity, a per charge range up to 10.5 miles and a maximum speed of 4.4 mph. Standard features include feather touch disassembly—which easily disassembles into 5 lightweight pieces for convenient transport and storage, wraparound delta tiller with charger port, non-scuffing black tires, LED headlight and front basket. Optional color shrouds available.





Go-Go® LX with CTS Suspension 3-wheel (Shown with optional Pearl Pink shrouds)

F

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®


THE RESERVE OF THE PROPERTY OF

facebook.com/PrideMobilityProductsCorp

pridemobility.com

#### **GO-GO®LX WITH CTS SUSPENSION** 3W: S50LX 4W: S54LX


Weight capacity:	300 lbs.
Maximum speed <sup>1</sup> :	Up to 4.4 mph
Ground clearance <sup>2</sup> :	1.5" at motor
Turning radius:	3W: 33" 4W: 44.75"
Overall length <sup>2</sup> :	3W: 39.75" 4W: 41"
Overall width <sup>2</sup> :	20.5"
Front tires:	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear tires:	2.5" x 8" solid
Range per charge <sup>1,4</sup> :	3W: Up to 9.44 miles 4W: Up to 10.5 miles
Total weight without batteries <sup>5</sup> :	3W: 85.4 lbs. 4W: 87.4 lbs.
Heaviest piece when disassembled:	3W: 34 lbs. (front section) 4W: 36.6 lbs. (front section)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Regenerative and electromechanical
Battery requirements <sup>3,5</sup> :	<ul> <li>(2) 12V Deep-cycle</li> <li>Size: (2) 12 AH-9 lbs. each or</li> <li>(2) 18 AH (optional)-14lbs. each</li> <li>Weight: 12 AH: 20 lbs. per battery pack,</li> <li>18 AH: 29.5 lbs. per battery pack</li> </ul>
Battery charger:	Off-board, 2 amp
Color:	Interchangeable Shrouds Optional















### **FEATURES**

- Comfort-Trac front and rear suspension for added comfort
- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- · Frame easily disassembles into 5 lightweight pieces for convenient transport and storage
- Stylish, lightweight, non-scuffing black low-profile tires
- Front frame-mounted seat post offers maximum stability
- Microprocessor-based controller offers optimal power management and added safety features
- Microprocessor-based controller offers optimal power management and added safety features
- Auto-connecting front to rear cable
- Standard front tiller-mounted basket
- · Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- · Includes 2 sets, 1 each of Red and Blue interchangeable color shroud panels
- Optional color shroud panels also available: Onyx Black, Orion Yellow, Pearl Pink, Sunburst Orange

## **Pride Lifts & Ramps**

### Compatible Lifts:

- Backpacker® Plus Outlander Full Platform
- Backpacker® AVP Outlander TM
- Olympian

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

### NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections



