

TRAVELMATE



CLASSIC FD



VIVA



RT EXPRESS



REAR DRIVE



HD



LIFT-ALL



ALERT LIGHT



Al Thieme was a young man working as a plumbing and heating contractor in Bridgeport, Mich. when a family member began to lose mobility due to multiple sclerosis. Witnessing this loss of independence, he created an innovative form of mobility.

Thieme went on to invent the first ever power-operated vehicle/scooter – the Amigo – in 1968. Hands-on and focused, he is passionate about *Improving Lives Through Mobility*®.



First Amigo



Are you ready to go?



Amigo Mobility International, Inc. manufactures a complete line of innovative mobility products including mobility power-operated vehicles and motorized shopping carts. Designed to bring comfort, freedom and satisfaction to customers, Amigo's quality, made in the USA products have been *Improving Lives Through Mobility*® since 1968.











AMIGO MOBILITY INTERNATIONAL, INC.
www.myamigo.com
1.800.MY.AMIGO
1.989.777.0910
info@myamigo.com
Bridgeport, MI USA



AMIGO MOBILITY INTERNATIONAL



Product Line

PRODUCT SPECIFICATIONS		TRAVELMATE	VIVA	CLASSIC FD	RT EXPRESS	REAR DRIVE	HD
Speed & Power	Speed Range • mph (kph)	FWD: 0-4.1 (6.6) high range / 0-3.0 (4.8) low range REV: 0-3 (4.8) high range / 0-2.5 (4.0) low range	0-5.0 (0-8)	0-4.1 (0-6.5)	0-5.0 (0-8)	0-5.9 (0-9.4)	0-5.0 (0-8)
	Standard Battery Capacity • miles* (km)	9.5 (15.2)	16 (25.7)	18 (28.9)	22 (35.4)	35 (56.3)	30 (48.2)
	Electrical System	24V	24V	24V	24V	24V	24V
	Battery AH	(2) standard 9 • (2) lithium 9.6	(2) 12 • (2) 7 Option	(2) 12	(2) 17	(2) 33 • 35	(2) 33 • 35
	Lithium-Ion Battery Capacity • miles* (km)	10 (16)					
	2A Universal Battery Charger with AC Cord	Offboard	Offboard	Offboard			
	3A Battery Charger with Retractable Cord				Onboard	Onboard	Onboard
	7A Universal Charger				Optional	Optional	Optional
Drive System	Type	Front Drive	Rear Drive	Front Drive	Rear Drive	Rear Drive	Rear Drive
Maneuverability	Vari-Speed	Standard	Standard	Standard	Standard	Standard	Standard
	Turning Radius • in (cm)	31 (78.7)	35 (88.9)	35 (88.9)	33 (83.8)	34 (84.3)	38 (96.5)
Dimensions	Underbody Ground Clearance • in (cm)	4 (10.1)	2.25 (5.7)	2.5 (6.3)	3 (7.6)	3.5 (8.8)	3.5 (8.8)
	Length • in (cm)	40.5 (102.8)	45 (114.3)	43.3 (109.9)	41.5 (105.4) • 38.5 (97.7) Shorter Platform	43.8 (111.2)	47.8 (121.4)
	Rear Wheel Width • in (cm)	22.4 (56.8)	22.5 (57.1)	21 (53.3)	20.5 (52)	23.5 (59.6)	23.5 (59.6)
	Height • in (cm)	35 (88.9)	36 (91.4)	37 (93.9)	34.7 (88.1) • 33 (83.8) Shorter Platform	37.8 (96)	39.5 (100.3)
	Weight with Batteries • lbs (kg)	69 (31.3)	116 (52.6)	102 (46.2)	130 (58.9) • 125 (56.6) Shorter Platform	162 (73.4)	186 (84.3)
	Weight without Batteries and Seat • lbs (kg)	57 (25.9) with Seat	73 (33.1)	58 (26.3)	76 (34.4) • 71 (32.2) Shorter Platform	92 (41.7)	100 (45.3)
	Handle Length • in (cm)	24 (61)	24.5 (62.2)	25 (63.5)	26.5 (67.3) • 26 (66) Shorter Platform	26 (66)	28 (71.1)
	Weight Capacity • lbs (kg)	250 (113.3)	250 (113.3)	250 (113.3)	250 (113.3)	350 (158.7)	500 (227)
Safety	Electromagnetic Braking with Manual Release	Standard	Standard	Standard	Standard	Standard	Standard
	Dynamic & Regenerative Braking	Standard	Standard	Standard	Standard	Standard	Standard
	Seat Lock		Standard	Standard	Standard	Standard	Standard
	Flip-Up, Adjustable, Removable Arms		Standard	Standard	Standard	Standard	Standard
	Rear Safety Bumper		Standard	Standard	Standard	Standard	Standard
	Anti-Tip Wheels		Standard	Standard	Standard	Standard	Standard
	Programmable Controller	Standard	Standard	Standard	Standard	Standard	Standard
	Protective Oval Handle		Standard	Standard	Standard	Standard	Standard
SmartSensor Anti-Impact System			Optional	Optional	Optional	Optional	
Platform	Platform Material	Aluminum	Steel	Steel	Steel	Steel	Steel
	Available Option				3 in Shorter	4 in longer	
Tires	Front Tire - Standard • in (cm)	8.5 x 2 (21 x 5) Solid Rubber	8 x 2 (20.3 x 5) Flat-Free	6 x 2 (15.2 x 5) Solid Foam Mag	6 x 2 (15.2 x 5) Solid Foam Mag	9 (22.8) Foam-Filled Mag	10 (25.4) Foam-Filled Mag
	Rear Tires - Standard • in (cm)	9 x 2.75 (23 x 7) Trimline, Solid Foam	9 (22.9) Trimline, Solid Foam	6 x 2 (15.2 x 5) Solid Foam Mag	9 (22.8) Trimline, Solid Foam	10.5 (26.6) Solid Foam Mag	10.5 (26.6) Solid Foam Mag
	Pneumatic Rear Mag Tires				Optional	Optional	Optional
	Pneumatic Front Mag Tires				Optional	Optional	Optional
	Trimline Rear Tires					Optional	Optional
	9 in (22.8 cm) Foam-Filled Mag Rear Tires		Optional		Optional		
Seat	Premier I		Optional	Standard	Standard	Standard	
	Travel Seat		Standard				
	Vinyl Low-back Seat	Standard					
	Cloth and Vinyl			Optional	Optional	Optional	
	All Vinyl 22 in (55.8 cm) Wide					Optional	Standard
	360 Degree Seat Rotation		Standard	Standard	Standard	Standard	Standard
	Power Seat Lift • up to 250 lbs (113.3 kg)			Optional	Optional**	Optional**	Optional**
	Power Seat Lift • up to 350 lbs (158.7 kg)					Optional**	Optional**
Tilt-In-Space • up to 250 lbs (113.3 kg)				Optional	Optional	Optional	
Shock Absorbing Seat Post • up to 250 lbs (113.3 kg)		Optional	Optional	Optional	Optional	Optional	
Handle	Hi/Lo Controls		Standard	Standard	Standard	Standard	Standard
	Touchtron Controls**			Optional	Optional	Optional	Optional
	Twist Grip	Standard					
Warranty	Platform and Seat Post	2 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime
	Motor, Controller, Charger	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years
	Seats and Other Components	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
	Batteries	6 Months	1 Year	1 Year	1 Year	1 Year	1 Year
Available Colors	 Moss Green		Moss Green				
	 Lime Green	Lime Green					
	 Classic Red				Classic Red	Classic Red	Classic Red
	 True Blue	True Blue			True Blue	True Blue	
	 White				White	White	
	 Midnight Black			Midnight Black	Midnight Black	Midnight Black	
	 Lemon Twist Yellow	Lemon Twist Yellow					
 Chili Pepper Red	Chili Pepper Red						