

The compact J6 is the ultimate choice for clients who demand the superb stability of Mid-Wheel 6® Design and tight-quarter maneuverability.

Highly adaptable, the J6 accepts a wide range of seating and electronics options while its powerful drivetrain delivers high-performance torque.

Manthurelab Colu



tre fright County by

## Specifications

opcomodiono	
DRIVE WHEELS	Standard: 10" Solid Optional: 10" Pneumatic
CASTER WHEELS	Front: 5" Solid Rear. 6" Solid
ANTI-TIP WHEELS	N/A
MAXIMUM SPEED <sup>4</sup>	Up to 4 mph
GROUND CLEARANCE	2.5" (frame)
TURNING RADIUS 5	22"
OVERALL LENGTH	34.74" without foot riggings
BASE WIDTH	23.19"
SEATING SIZES	
Synergy®/TRU-Balance® 2 Static Seat	Width: 10-20" Depth: 10-20"
TRU-Balance® 2 Power Tilt	Width: 14-20" Depth: 14-20"
TRU-Balance® 2 Lift & Tilt	N/A
SEAT-TO-FLOOR HEIGHTS	
Synergy®/TRU-Balance® 2 Static Seat 8	16.5-17.5"
TRU-Balance® 2 Power Tilt 8	16.875"
TRU-Balance® 2 Lift & Tilt 8	N/A
MANUAL TILT/RECLINE 10	Yes
BATTERY SIZE <sup>6</sup>	U-1
BATTERY WEIGHT <sup>14</sup>	23.4 lbs.
AVAILABLE ELECTRONICS 12	70A Q-Logic 2 NE 70A Q-Logic 2 NE+ 70A Q-Logic 2 EX
BATTERY CHARGER	5A Off-board
MOTOR PACKAGES	2-Pole 4 mph
WEIGHT CAPACITY 7	300 lbs. <sup>9</sup>
BASE WEIGHT	100.2 lbs.
MEDICARE CODE COVERAGE	Group 2: Standard (K0822/K0823), Single Power (K0835)

- 1) Standard
- 2) Optional
- 4) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- 5) Without front riggings
- 6) Battery capacity may change when adding power positioning systems.
- 7) Weight capacity is dictated by the selection of seating.
- 8) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 9) 250 lbs. weight capacity with TRU-Balance® Systems
- 10) The Synergy  $^{\rm S}$  Manual Tilt weight capacity is 75 lbs. and maximum dimensions are 14" W x 14" D. Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
- 11) Requires Group 34 batteries
- 12) All Quantum Rehab® units can be ordered with specialty controls
- 13) Required with high-speed motors
- 14) Battery weight may vary +/- 3 lbs. based on manufacturer.

## Features

- Mid-Wheel 6<sup>®</sup> allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance<sup>®</sup> 2 Tilt <sup>5</sup>
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates enhanced performance over more varied terrain
- Easy front access to batteries

## Options

- Swing-away joystick mount
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves

- Gel adductor buttons
- Power elevating seat
- Angle-adjustable footplates
- 70° swing-away leg rests
- Q-Logic 2 EX Drive Control System

## Colors



Candy Apple Red



Viper Blue



(US) 866-800-2002 • (CAN) 888-570-1113 • www.quantumrehab.com • www.ilevel.rehab









