

There is Power Mobility. And then there's

# POWERFUL MOBILITY



Call 1-800-944-1997 or visit us at [www.evrider.com](http://www.evrider.com)

# There is Power Mobility. And then there's **POWERFUL MOBILITY**



with optional windshield and travel case

Ground Clearance	5" in / 13 cm
Length - Overall	62" in / 170 cm
Width - Overall	29" in / 74 cm
Height - Overall	45" in / 115 cm
Height - Deck	7.5" in / 19 cm
Height for Transport - Minimum	44" in / 112 cm - Top of Tiller
Height - Seat Cushion	16" in to Deck / 24" in to Floor
Seat - Width & Depth & Height	20" in W x 22" in Depth x 31" in H 51 cm W x 56 cm Depth x 79 cm H
Turning Radius	43" in / 109 cm
Tire Type	Road Rated Pneumatic Tires
Rim Type	Aluminum Alloy Rims
Wheelbase for Lifts	44" in / 112 cm Long // 26" in / 66 cm Wide
OEM Spec	2.75-14
Width - Tire	3" in / 8 cm
Max PSI	40
Weight with Batteries	410 lbs / 186 kgs G-24 (79Ah) Batteries // 430 lbs / 195 kgs G-27 (100Ah) Batteries

Weight without Batteries	306 lbs / 132 kgs
Battery Type & Power (Recommended / 2 Required)	Sealed Lead Acid (SLA) - AGM // Group 24 & Group 27 (100 Amp Hrs)
Brake System	Electromagnetic
Climbing Angle (Maximum Recommended)	12°
Charger Type	8 amp / Off-Board (120 / 50/60 Hz)
Charging Time	6 - 8 hrs
Controller	160 amp / Dynamic Rhino
*Driving Range	20 - 25 miles / 32 - 40 km with Group 24 Batteries 25 - 30 miles / 40 - 48 km with Group 27 Batteries
Load Capacity	450 lbs / 204 kgs
Motor / Transaxle	1300W - 4 Pole Brush Motor 15K Transaxle
*Speed - Maximum	9.3 mph / 15 kmh
Basket Type, Color & Size - Optional (Included) ***	Wire Rear Basket
Basket Type, Color & Size - (Optional) ***	Wire Basket - Black / Large Travel Case - Black / Lg & Extra Large
Color	Black & Chrome

Control - Display Type	Digital w/Navigation Back Lighting
Cup Holder	Optional
Mirrors	Left Side Rear View
Leg Room	20" / 51 cm
Light Type	LED Headlights // Taillights w/Turn Signals
Seat Type	Captain Seat-Contoured Orthopedic
Seat Features	Captain Seat - High Back/Slide & Swivel
Seat Swivel	360°
Suspension	Full Front & Rear
Tiller Type	Infinite Adjustment
Throttle Control Type	Single - One Hand**

(\*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.

(\*\*) THROTTLE CAN BE CONVERTED TO LEFT HAND OPERATION.

Call **1-800-944-1997** or visit us at **www.evrider.com**