

There is Power Mobility. And then there's
**POWERFUL
MOBILITY**



transport

Call **1-800-944-1997** or visit us at www.evrider.com

There is Power Mobility. And then there's **POWERFUL MOBILITY**



Ground Clearance	2.4"
Length - Overall	36"
Width - Overall	21"
Height - Overall	37 ½"
Overall Height - at Minimum Tiller Height	31"
Legroom - Floorboard Length x Width	19" x 13"
Height - Deck	6.5"
Turning Radius	32.3"
Folded Overall Length	31"
Folded Overall Width	19"
Folded Overall Height	18"
Weight with Std. 12V12Ah Batteries	70 lbs
Weight with Opt. 112V11.5Ah Li Ion Batteries	60 lbs
Weight without Batteries	53 lbs
Seat Type	Folding backrest, ABS plastic with high density foam cushion

Seat - Width & Depth & Height	16" x 13½" x 13½"
Seat - Cushion Thickness	1"
Seat Height - Cushion to Deck	14"
Seat Height - Cushion to Floor	20.5"
Tire Type	Solid rubber front and rear
Rim Type Rear	Cast Aluminum
Rim Type Front	ABS Plastic
OEM Spec Rear	200 x 50
Outside Diameter Rear	8"
OEM Spec Front	180/40
Outside Diameter Front	7"
Tire Width Front	1.6"
Tire Width Rear	2"
Battery Type & Power	Std. Two 12V12Ah SLA Optional 24V11.5Ah Li Ion Battery Pack
Brake System	Electromagnetic Brake

Climbing Angle - Maximum Recommended	6 degrees
Charger Type	2 Amp, 110/240 Volt SLA Charger 2.5Amp, 110/240 Volt, Li-ION Charger
Charging Time	4 - 6 hours
Controller	S-Druive 45 Amp
*Driving Range	10 - 15 miles
Load Capacity	250 lbs (115 kgs)
Motor & Drive Location	4-pole, 270 Watt, Rear-Wheel Drive
*Speed - Maximum	4 mph
Colors	Metallic Paradise Blue with Metallic Silver Accents, Plum
Tiller Type	Height Adjustable
Throttle Control Type	Digital Wig-Wag
Anti-Tipper Wheels-Rear	Standard

(*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.

Call 1-800-944-1997 or visit us at www.evrider.com