

### 3 & 4-WHEEL SCOOTER

# COMFORT AND PERFORMANCE FOR YOUR ACTIVE LIFESTYLE.

The **Victory**® series line of mobility scooters offer a perfect balance of style, comfort and performance for your active lifestyle. The **Victory® 9** features one-hand feather touch disassembly, wraparound delta tiller, 300 lb. weight capacity, a per charge range up to 13 miles and a maximum speed up to 5.25 mph. Standard features include, 9" solid tires, LED lighting package, backlit battery gauge and a front basket. Available in Viper Blue and Candy Apple Red.





Victory® 9 (4-Wheel)

Victory® 9 (3-Wheel)



facebook.com/PrideMobilityProductsCorp



youtube.com/PrideMobility



# **SPECIFICATIONS**

#### VICTORY® 9 3-Wheel (3W): SC609 4-Wheel (4W): SC709

Weight capacity:	300 lbs.
Maximum speed <sup>1</sup> :	Up to 5.25 mph
Ground clearance <sup>3</sup> :	3W: 2" 4W: 2.25"
Turning radius <sup>3</sup> :	3W: 40.25" 4W: 51.5"
Overall length <sup>3</sup> :	3W: 43.5" 4W: 45.5"
Overall width <sup>3</sup> :	3W: 22.25" 4W: 22.5"
Seat-to-deck height <sup>3</sup> :	17.25"-18.75"
Seat-to-ground height range:	19.25"-20.75"
Front tires:	3W: 3" x 8" solid 4W: 3" x 9" solid
Rear tires:	3" x 9" solid
Range per charge <sup>1,2</sup> :	Up to 13 miles
Total weight without batteries <sup>1,3</sup> :	3W: 117.5 lbs. 4W: 131 lbs.
Heaviest piece when disassembled <sup>3,6</sup> :	3W: 48.5 lbs. (front section) 4W: 59 lbs. (front section)
Standard seating:	Type: Foldable molded plastic Weight: 28 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive system:	Rear-wheel drive, sealed transaxle with 24-volt DC moto
Dual braking system:	Electronic, regenerative and electromechanical
Battery requirements <sup>4,5</sup> :	(2) 12V deep-cycle Size: U-1 Weight: (U-1) 24.5 lbs. each
Battery charger:	3-amp, off-board

## Color:







Candy Apple Red

Viper Blue

- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
   Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- perioritarice: ests conduced a maximum weight capacity.
  3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 AGM or gel cell type required.
- 5 Battery weight may vary based on battery manufacturer.
  6 Includes standard seat weight.

#### NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

# **FEATURES**

- · Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- · Delta tiller with wraparound handles
- · Backlit battery gauge
- · Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- · Lightweight pinchless hinge seat, eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port
- · Auto-connecting front-to-rear harness

#### **OPTIONS**

- · Forearm crutch holder
- · Cane/crutch holder
- · Oxygen tank holder
- Cup holder
- · Rear basket
- Safety flag
- Walker holder
- · Weather cover
- Saddlebag
- Rear view mirror
- Lapbelt
- · Cell phone holder
- · Touch up paint

# **Pride Lifts & Ramps**

# Compatible Lifts:

Backpacker® Plus
 Outlander



